

Petroleum Transfer Hose

Gasflex® Curb Pump (Hard Wall) (Specification 3624)



Nom. I.D.		Nom. O.D.		Maxi. W.P.		Suction		Min. Bend Radius		Kg. Per	Standard Pack	Part No.
(In.)	(mm)	(In.)	(mm)	(psi)	(Mpa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(m.)	(m.)	
5/8	16.0	1.00	25.4	250	1.70	30.0	762	6.0	152.0	0.609	117	3624-0814
3/4	20.0	1.26	32.0	250	1.70	30.0	762	6.0	152.0	0.917	137	3624-0815
1	25.0	1.49	38.0	250	1.70	25.0	635	8.0	203.0	1.107	76	3624-0816

Recommended for:

Dispensing all types of commercial petrol's, or other petroleum based products, from service station pumps.

Gasflex Curb Pump is a heavy duty hard wall hose which does not collapse in reel use or behind the nozzle in heavy duty service.

Temperature: -30°C to +49°C continuous service.

Construction:

Tube: Nitrile. Black.

Reinforcement: Braided, high tensile steel wire.

Cover: Modified Nitrile. Black.

Packaging:

5/8": Packaged 117m per reel.

3/4": Packaged 137m per reel

1": Packaged 76m per reel

Branding:

Offset ink print.

Example:  16mm GASFLEX Petrol Pump Hose

AS 2683/2000 Type 4 grade 2 kind 1 and 2 WP 250PSI

MADE IN INDIA.

Standards:

AS 2683/2000 Type 4 grade 2 kind 1 & 2