

9mm L-band Worm-drive Hose clip **W4**



DIN: 3017 Light series

Asfa-L W4 Hose Clip (9 mm bandwidth)

Information	Ø Application mm	Reference W4	L max.	s ± 0,05	h max.	a ± 0,3 ± 0,2	b max.	Max. Values* Torque Nm	Max. Values* Pressure (Bars)	Box Quantity	Packing
Thanks to the exclusive design of the housing, the ASFA-L W4 hose clip has excellent performance while being at the same time very compact. The cold-formed stamped band thread, smoothed on the underside, combined with beveled band-edges protects the hose from damage. The ASFA-L W4 hose clip complies fully with the DIN 3017 norm and also with the RoHs directive EU 20032/95/EC dated 1st July 2006. This clip is ideally for use in the marine industry, due to the corrosion resistance offered by the use of AISI-304 stainless steel in its manufacture.	8-16	03014019	22,1	0,6	10	9	14	3,0	45	200	800
	12-22	03014027	22,1	0,6	10	9	14	3,0	45	200	800
	16-27	03014035	23,6	0,7	10	9	14	3,5	42	200	800
	20-32	03014043	23,6	0,7	10	9	14	3,5	36	200	800
	25-40	03014051	25,6	0,7	10	9	14	4,0	32	100	800
	30-45	03014060	25,6	0,7	10	9	14	4,0	28	100	800
	32-50	03014078	25,6	0,7	10	9	14	4,0	24	100	800
	40-60	03014086	25,6	0,7	10	9	14	4,0	19	100	400
	50-70	03014094	26,6	0,7	10	9	14	4,0	17	100	100
	60-80	03014107	26,6	0,7	10	9	14	4,0	15	100	100
	70-90	03014115	26,6	0,7	10	9	14	4,0	13	50	400
	80-100	03014123	26,6	0,7	10	9	14	4,0	11	50	400
	90-110	03014140	26,6	0,7	10	9	14	4,0	10	25	200
	100-120	03014158	26,6	0,7	10	9	14	4,0	9	25	200
	110-130	03014166	26,6	0,7	10	9	14	4,0	8	25	25
	120-140	03014174	26,6	0,7	10	9	14	4,0	7	25	25
130-150	03014182	26,6	0,7	10	9	14	4,0	6	25	25	
140-160	03014190	26,6	0,7	10	9	14	4,0	5	25	25	

*The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.

Patented Worldwide.

Materials W4

Screw:
AISI-304 Cu
Stainless steel

Band and Housing:
X5CrNi1810
Stainless steel
(DIN 1.4301)
(AISI-304)

