

# VISCOTROLL The Original

## Independent mobile unit for oil transfer

Viscotroll DC is the ideal solution for dispensing oil any time, anywhere, without using compressed air or power mains. The unit includes a self-priming gear pump with a 12-VDC electric motor. The built-in pressure switch allows the pump to be automatically started and stopped. A nozzle meter monitors any dispensed quantity. The unit has a built-in battery charger. Battery must be recharged after transferring 2/3 oil drums. A unique solution to an ever-increasing demand from automotive transport workshops and for maintenance.


## Performances

- Flow rate up to 9 l/min
  - Noise levels less than 65 dB
  - Motor supply 12 Vdc
  - Oil viscosity from up to 2000 cSt
  - On demand dispensing with pressure switch
  - Flow meter with a meter precision of +/- 0.5 %
- Specifications
- Tubular structure trailer-mounted support for moving drums, complete with nozzle support, pipe support and drip collector.
  - Self-priming pump with dc motor, 12 Vdc protection rating IP 55.

- 3/4 " GAS suction hose with filter.
- 4 meters long 1/2 " GAS delivery hose
- Delivery nozzle with meter, flexible end with non-drip valve
- Pressure switch with incorporated safety valve
- Battery with battery charger (at 220-240V Vac 50-60Hz, max absorb. Amp. 0.6; at 85-125V Vac 50-60Hz, max absorb. Amp. 1,1)

## Options:

- Flow meter with oval gears
- AC motor



On demand dispensing

Drum not included

## VISCOTROLL DC

Flow rate up to 6 l/min  
Accuracy ± 0,5 %  
Viscosity up to 2000 cSt



Gear pump

Integrated battery charger



## VISCOTROLL AC

Flow rate up to 9 l/min  
Accuracy ± 0,5 %  
Viscosity up to 2000 cSt

## VISCOTROLL

Code	Description	Flow rate		DC Volt	AC Volt	Battery charger V	Pressure switch	Easyoil Nozzle	K400 Meter	Weight Kg	Packaging mm
		l/min	gal/min								
F00263200	Viscotroll DC 120/1 pst.	6	1,6	12	-	230	•	•	•	57	1090x690x320
F00263210	Viscotroll DC 120/1 pst. K400	6	1,6	12	-	230	•	•	•	58	1090x690x320
F00263220	Viscotroll DC 120/1 pst. K400 100V/110V	6	1,6	12	-	110	•	•	•	58	1090x690x320
F0026300A	Viscotroll AC 200/2	9	2,4	-	230	-	-	•	-	34	1090x690x300
F0026301A	Viscotroll AC 200/2 - K400	9	2,4	-	230	-	-	•	•	35	1090x690x300
00026302A	Viscotroll AC 200/2 - PST	9	2,4	-	230	-	•	•	-	36	1090x690x300
00026303A	Viscotroll AC 200/2 - PST - K400	9	2,4	-	230	-	•	•	•	37	1090x690x300