



R X Plastics Pty Ltd
 P.O.Box 519
 Virginia Queensland 4014
 Australia
 Ph: +61 7 38658733
 Fax: +61 7 38653488
 e-mail: info@rxplastics.com.au

Flexible Reinforced PVC Hoses

Fire Reel Hoses

Features

- Excellent U.V. / Resistance
- Excellent abrasion resistance
- Outstanding flexibility
- Complies to Australian Standard AS1221
- Manufactured with a 4:1 safety factor

Construction

- Inner core: Black PVC with a seamless smooth finish
- Reinforcing: High tenacity polyester yarn
- Outer cover: U.V. stabilised black PVC with a ribbed finish



Nom ID	Nom OD	Working Pressure*	Stock Lengths
19mm	26mm	1.2 MPa	20m, 36m, 100m
25mm	34mm	1.2 MPa	20m, 100m

*at 20° Celsius

Farmflex (Drum Pump) Hose

Features

- Excellent U.V. /Resistance
- Extremely flexible even at low temperatures
- Manufactured using a PVC/Rubber blend
- Recommended for use in the gravity transfer of diesel/fuel

Construction

- Inner core: Black PVC/Rubber blend with a smooth finish.
- Reinforcing: High tenacity polyester yarn
- Outer cover: U.V. stabilised black PVC/Rubber blend with a smooth finish.



Nom ID	Nom OD	Working Pressure*	Stock Lengths
25mm	34.2mm	1 MPa	20m, 100m
31.5mm	42.5mm	1 MPa	20m, 60m

*at 20° Celsius