

SUNNYHOSE



- Sunnyhose has the largest market share worldwide because users appreciate its high quality and economy. It is made of synthetic fibers and soft PVC in a continuous/one process production developed by Takata Corporation. It is a general purpose hose, consistently high in quality, and available in long lengths. It is designed for temporary water supply or drainage, for drip irrigation and sprinkler irrigation at farms.
- The large diameter Sunnyhose, 250 ~ 400mm, is ideal for use as drainage hose in emergency/flood/disaster situations when large quantities of water must be moved quickly.



Size (mm/inches)	Inside Diameter (mm)	Wall Thickness (mm)	Weight (g/m)	Working Pressure (kg/cm ²)
40 (1.5)	41	1.25	205	5.0
50 (2)	53	1.30	270	4.5
65 (2.5)	66	1.50	380	4.0
75 (3)	78	1.70	530	4.0
100 (4)	104	1.75	705	4.0
125 (5)	128	1.85	935	3.0
150 (6)	155	1.95	1,175	3.0
200 (8)	207.5	2.20	1,785	3.0
250 (10)	257	2.65	2,650	2.5
300 (12)	308	2.55	2,910	2.0
350 (14)	359	2.70	3,650	2.0
400 (16)	410	2.70	4,287	2.0

*Standard length:100m. (10m, 20m, 30m, 50m are available on request)
 *Working pressure: 200C